GE Zoneline® Heat Pump Unit with Makeup Air 12,000 BTU, 230/208 Volt



Model# AZ65H12DBM

Control Type	Standard Microcomputer; Tactile touch pad with LED Display
Product Type	Packaged Terminal Air Condition (PTAC)
Refrigerant Type	R410A
Temperature Range	60 - 85 F
Fan Speed Selections	Hi/Low Cooling; Hi/Low Fan Only Hi/Low Heating
Fan Speed Control	Yes
Electronic Micro Computer Control	Yes
Filter Type	Rigid Frame; Slide-Out
Chassis Type	Slide-In
Fan Cycle Switch	Yes
Heat - Cool	Yes
Heating - Reverse Cycle - COP	3.5/3.5
Rotary Compressor	Yes
Sensible Heat Ratio	69%
	Cycle Control; 3-Stage Heating Design; Auto Power Recovery; Automatic Emergency Heat; Automatic Indoor Frost Control; Central Desk Control Compatibilise Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangentic Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weat Protected Electrical Components
Discharge Grille	2-position
Fan Motor	2
Temperature Limiting	Electronic 7-Step
Heating System	Heat Pump
Power Factor	97
Louver Style	Reversible
Makeup Air	

GE Zoneline® Heat Pump Unit with Makeup Air 12,000 BTU, 230/208 Volt



Model# AZ65H12DBM

APPROXIMATE DIMENSIONS (HxDxW)

• 16 in x 20 13/16 in x 42 in

CAPACITY

- CFM Indoor Fan High 449
- Cooling EER (BTUH / Watt) 11.2/11.2
- Dehumidification (pts./hr.) 3.40
- Vent CFM (high fan at zero ESP) 25-50
- Heating Reverse Cycle BTUH 10200/10000
- CFM Indoor Fan Low 300
- Cooling BTUH (MAX) 11500.00 Btu
- Cooling BTUH (MIN) 11400.00 Btu

WARRANTY

- Labor Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Parts Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Warranty Notes See written warranty for full details