GE Zoneline® Cooling and Electric Heat Unit with Corrosion Protection 15,000 BTU, 230/208 Volt

Model# AZ45E15DAC

FEATURES

Control Type	Coverless Backlit White LED Touch Controls
Product Type	Packaged Terminal Air Conditioners (PTAC)
Refrigerant Type	R410A
Temperature Range	60 - 85 F
Fan Speed Selections	Hi/Low Cooling; Hi/Low Fan Only; Hi/Low Heating
Fan Speed Control	Yes
Electronic Micro Computer Control	Yes
Filter Type	Rigid Frame; Slide-Out
Chassis Type	Slide-In
Fan Cycle Switch	Yes
Heat - Cool	Yes
Manual Vent Control	Hidden
Rotary Compressor	Yes
Sensible Heat Ratio	63%
Venting Features	Concealed Manual Vent Control¶Vent Air Filter¶Outdoor Vent Control - 3 Positions
Zoneline Features	"Sleep" Mode; "Smart Fan" Fan Cycle Control; Auto Power Recovery; Automatic Indoor Frost Control; Central Desk Control Compatibility; Freeze Sentinel; Heat Sentinel (85F); Proportional - Integral ID Airflow; Random Twist/ Length Segment Tangential Blower; Remote Thermostat Compatibility; Universal Heaters; Weather Protected Electrical Components
Discharge Grille	2-position
Fan Motor	2
Temperature Limiting	Electronic 7-Step
Vent Control	3-position
Heating System	Electric Resistance
Power Factor	97
Louver Style	Reversible
Corrosion Treated	Yes

Have more questions? Please contact 1-800-626-2005

GE Zoneline® Cooling and Electric Heat Unit with Corrosion Protection 15,000 BTU, 230/208 Volt

Model# AZ45E15DAC

APPROXIMATE DIMENSIONS (HxDxW)

- **16 in x 20 13/16 in x 42 in**

CAPACITY

- **CFM Indoor Fan High 436**
- **Cooling EER (BTUH / Watt) 10.5/10.5**
- **Dehumidification (pts./hr.) 4.60**
- **Vent CFM (high fan at zero ESP) 47**
- **CFM Indoor Fan Low 330**
- **Cooling BTUH (MAX) 14000.00 Btu**
- **Cooling BTUH (MIN) 13900.00 Btu**

WARRANTY

- **Labor Warranty - Limited 1-year entire appliance; Limited 5-year sealed refrigerating system**
- **Parts Warranty - Limited 1-year entire appliance; Limited 5-year sealed refrigerating system**
- **Warranty Notes - See written warranty for full details**

Have more questions? Please contact 1-800-626-2005