GE Zoneline® Heat Pump Unit with Corrosion Protection 7,000 BTU, 230/208 Volt



Model# AZ65H07DAC

Control Type	Standard Microcomputer; Tactile
0 1 17	touch pad with LED Display
Product Type	Packaged Terminal Air Conditions (PTAC)
Refrigerant Type	R410A
Temperature Range	60 - 85 F
Fan Speed Selections	Hi/Low Cooling; Hi/Low Fan Only Hi/Low Heating
Fan Speed Control	Yes
Electronic Micro Computer Control	Yes
Filter Type	Rigid Frame; Slide-Out
Chassis Type	Slide-In
Fan Cycle Switch	Yes
Heat - Cool	Yes
Heating - Reverse Cycle - COP	4.0/4.0
Manual Vent Control	Hidden
Rotary Compressor	Yes
Sensible Heat Ratio	73%
Venting Features	Concealed Manual Vent
	Control¶Vent Air Filter¶Outdoor
	Vent Control - 3 Positions
Zoneline Features	"Sleep" Mode; "Smart Fan" Fan
Zonemie rediales	Cycle Control; 3-Stage Heating Design; Auto Power Recovery; Automatic Emergency Heat; Automatic Indoor Frost Control; Central Desk Control Compatibilit
Discharge Grille	Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangentia Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weath Protected Electrical Components
Discharge Grille	Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangentia Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weatl Protected Electrical Components 2-position
Fan Motor	Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangentia Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weatl Protected Electrical Components 2-position
Fan Motor Temperature Limiting	Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangentia Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weatl Protected Electrical Components 2-position 2 Electronic 7-Step
Fan Motor Temperature Limiting Vent Control	Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangentia Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weatl Protected Electrical Components 2-position 2 Electronic 7-Step 3-position
Fan Motor Temperature Limiting Vent Control Heating System	Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangentia Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weatl Protected Electrical Components 2-position 2 Electronic 7-Step 3-position Heat Pump
Fan Motor Temperature Limiting Vent Control	Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangentic Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weatl Protected Electrical Components 2-position 2 Electronic 7-Step 3-position

GE Zoneline® Heat Pump Unit with Corrosion Protection 7,000 BTU, 230/208 Volt



Model# AZ65H07DAC

APPROXIMATE DIMENSIONS (HxDxW)

• 16 in x 20 13/16 in x 42 in

CAPACITY

- CFM Indoor Fan High 360
- Cooling EER (BTUH / Watt) 13.0/13.0
- Dehumidification (pts./hr.) 1.60
- Vent CFM (high fan at zero ESP) 38
- Heating Reverse Cycle BTUH 6200/6100
- CFM Indoor Fan Low 205
- Cooling BTUH (MAX) 7100.00 Btu
- Cooling BTUH (MIN) 7000.00 Btu

WARRANTY

- Labor Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Parts Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Warranty Notes See written warranty for full details