

# GE PROFILE™ REVERSE OSMOSIS PREMIUM WATER FILTRATION SYSTEM



Model# PXRQ15RBL



- Reverse osmosis filtration - Water is filtered three times
- Chrome faucet with filter replacement indicator - Faucet and full installation kit included
- Premium filtration - Certified to reduce lead, arsenic, select chemicals, and 10 other contaminants
- Twist and lock design - Provides for easy, tool-free, no-mess filter replacement
- Six-month filter life - For best filtration results, filters (FQROPF) should be replaced every six months

## FEATURES

Feed Water pH Limits	4-10
Feed Water Pressure (psi)	40 Min - 125 Max.
Feed Water Temperature	40-100 F
Filter Cartridge	Carbon Block
Filter Change Indicator	LED
NSF Particulate Reduction	Class III
Plumbing Connections	1/4" Inlet - 3/8" Outlet
Faucet Monitor	Electronic Timer
Filter Life	6 Months or 900 gallons
Max. Filtered Water Flow (gpm)	0.75
Max. Hardness	10 Grains @ 6.9 pH
Max. TDS (ppm)	2000
Style	Quick Replace
Automatic Shut-Off	Yes
Filter	FQROPF
Filter Membrane	FQROMF
LED Indicators	Yes
Process Water Used (per gal.)	10
Water Inlet Valve	1/2" & 3/8" NPT ball valve adaptor
Arsenic Reduction	98%
Asbestos Reduction	99.9%
Chlorine Taste and Odor Reduction	96.1%
Chromium III Reduction	96.5%
Chromium VI Reduction	97.5%
Copper Reduction	97.5%
Cysts Reduction	99.99%
Lead Reduction	97.6%
Sodium Reduction	91.6%
TDS Reduction	91.6%
TDS Removal	91.6%
Turbidity Reduction	99.9%
Fittings	1/4" - Push to Connect

Have more questions? Please contact 1-800-626-2005

# GE PROFILE™ REVERSE OSMOSIS PREMIUM WATER FILTRATION SYSTEM



Profile™ Series

Model# PXRQ15RBL

## APPROXIMATE DIMENSIONS (HxDxW)

- 12 in x 4 1/2 in x 11 in

## CAPACITY

- Filtered Water Output 8.50 gal/day
- Storage Tank Capacity (gals.) 4\* (\*Theoretical tank capacity. When tested according to NSF/ANSI 58 at 50 PSIG inlet pressure, tank capacity is 2.3 gallons)
- Pre/Post Filter Life 900 Gallons

## WARRANTY

- Parts Warranty - Limited 1-year entire appliance
- Warranty Notes - See written warranty for full details

Have more questions? Please contact 1-800-626-2005